KACO new energy.

blueplanet 125 - 150 TL3

String inverters for utility-scale solar power plants up to multi-megawatt solar parks.



Decentrally into new dimensions.

Superior efficiencies and overload capacity through silicon carbide technology

Special properties for extreme environmental conditions

Decentralised design or ‚Virtual Central' concept possible

Overvoltage protection AC/ DC and for communication interfaces available

Lean commissioning and updates via remote services

EUPD RESEARCH TOP BRAND PV INVERTERS EUROPE 2021

www.kaco-newenergy.com

Technical Data

DC input data	125 TL3 US-S	125 TL3
Max. recommended PV generator power	187 500 W	187 500 W
MPP range	875 – 1 300 V	875 – 1 300 V
Operating range	875 – 1 450 V	875 – 1 450 V
Rated DC voltage / start voltage	900 V / 1 000 V	900 V / 1 000 V
Max. no-load voltage	1 500 V	1 500 V
Max. input current	160 A	160 A
Max. short circuit current $I_{sc\ max}$	300 A	300 A
Number of MPP tracker	1	1
Connection per tracker	1 - 2	1 - 2
AC output data		
Rated output	125 000 VA	125 000 VA
Max. power	125 000 VA	137 500 VA
Line voltage	600 V (3P+PE)	600 V (3P+PE)
Voltage range (Ph-Ph)	450 – 690 V	450 – 690 V
Rated frequency (range)	50 Hz / 60 Hz (45 – 65 Hz)	50 Hz / 60 Hz (45 – 65 Hz)
Rated current	3 x 120.3 A	3 x 120.3 A
Max. current	3 x 120.3 A	3 x 132.3 A
Reactive power / cos phi	0 – 100 % Snom / 0,30 ind. – 0,30 cap.	
Max. total harmonic distortion (THD)	≤ 3 %	≤ 3 %
Number of grid phases	3	3
General data		
Max. efficiency	99.2 %	99.2 %
Europ. efficiency	99.0 %	99.0 %
CEC efficiency	98.9 %	98.9 %
Standby consumption	< 10 W	< 10 W
Circuitry topology	transformerless	transformerless
Mechanical data		
Display	LEDs	LEDs
Control units	webserver, supports mobile devices	webserver, supports mobile devices
Interfaces	Ethernet (Modbus TCP, Sunspec),RS485 (KACO-protocol) USB, optional: 4-DI	
Fault signalling relay	potential-free NOC max. 30 V / 1 A	potential-free NOC max. 30 V / 1 A
DC connection	cable lug, max. 240 mm² (0.372 in²) Cu or Al	
AC connection	cable lug, max. 240 mm² (0.372 in²) Cu or Al	
Ambient temperature	-25 °C – +60 °C [1]	-25 °C – +60 °C [1]
Humidity	0 – 100 %	0 – 100 %
Max. installation elevation (above MSL)	3 000 m	3 000 m
Min. distance from coast	500 m	500 m
Cooling	temperature controlled fan	temperature controlled fan
Protection class	IP66 / NEMA 4X	IP66 / NEMA 4X
Noise emission	59.2 db (A)	59.2 db (A)
H x W x D	719 x 699 x 460 mm	719 x 699 x 460 mm
Weight	78.2 kg	78.2 kg
Certifications		
Safety	IEC 62109-1/-2, EN 61000-6-1/-2/-4, EN 61000-3-11/-12, EN 55011 group 1, class A EN 62920 Emission class A/Immunity class A UL62109-1, UL1741 Sup SB CSA-C22.2 No.107.1 CSA-C22.2 No.62109-1, CSA-C22.2 No.62109-2	UL1741 Sup SA/SB
Grid connection rule	overview see homepage/download area	

[1] derative derating at high ambient temperatures

Versions	S	XL
Number of DC inputs	1 - 2	1 - 2
DC switch	-	✓
DC SPD	Type 1 + 2	Type 1 + 2
AC SPD	○	○
RS485 interface SPD	○	○
Ethernet interface SPD	○	○
PID Set	○	○

standard = ✓ upgradeable = ○

Technical Data

DC input data	137 TL3	150 TL3
Max. recommended PV generator power	205 500 W	225 000 W
MPP range	875 – 1 300 V	960 – 1 300 V
Operating range	Operating range	960 – 1 450 V
Rated DC voltage / start voltage	Rated DC voltage / start voltage	1 000 V / 1 100 V
Max. no-load voltage	Max. no-load voltage	1 500 V
Max. input current	Max. input current	160 A
Max. short circuit current $I_{sc\ max}$	Max. short circuit current $I_{sc\ max}$	300 A
Number of MPP tracker	Number of MPP tracker	1
Connection per tracker	Connection per tracker	1 - 2
AC output data		
Rated output	137 000 VA	150 000 VA
Max. power	137 500 VA	150 000 VA
Line voltage	600 V (3P+PE)	660 V (3P+PE)
Voltage range (Ph-Ph)	480 – 690 V	480 – 760 V
Rated frequency (range)	50 Hz / 60 Hz (45 – 65 Hz)	50 Hz / 60 Hz (45 – 65 Hz)
Rated current	3 x 132.3 A	3 x 131.2 A
Max. current	3 x 132.3 A	3 x 132.3 A
Reactive power / cos phi	0 – 100 % Snom / 0,30 ind. – 0,30 cap.	0 – 100 % Snom / 0.30 ind. – 0.30 cap.
Max. total harmonic distortion (THD)	≤ 3 %	≤ 3 %
Number of grid phases	3	3
General data		
Max. efficiency	99.2 %	99.2 %
Europ. efficiency	99.0 %	99.0 %
CEC efficiency	98.9 %	99.0 %
Standby consumption	< 10 W	< 10 W
Circuitry topology	transformerless	transformerless
Mechanical data		
Display	LEDs	LEDs
Control units	webserver, supports mobile devices	webserver, supports mobile devices
Interfaces	Ethernet (Modbus TCP, Sunspec), RS485 (KACO-protocol)	Ethernet (Modbus TCP, Sunspec), RS485 (KACO-protocol)
Fault signalling relay	potential-free NOC max. 30 V / 1 A	potential-free NOC max. 30 V / 1 A
DC connection	cable lug, max. 240 mm² (0.372 in²) Cu or Al	cable lug, max. 240 mm² (0.372 in²) Cu
AC connection	cable lug, max. 240 mm² (0.372 in²) Cu or Al	cable lug, max. 240 mm² (0.372 in²) Cu
Ambient temperature	-25 °C – +60 °C [1)]	-25 °C – +60 °C [1)]
Humidity	0 – 100 %	0 – 100 %
Max. installation elevation (above MSL)	3 000 m	3 000 m
Min. distance from coast	500 m	500 m
Cooling	temperature controlled fan	temperature controlled fan
Protection class	IP66 / NEMA 4X	IP66 / NEMA 4X
Noise emission	59.2 db (A)	59.2 db (A)
H x W x D	719 x 699 x 460 mm	719 x 699 x 460 mm
Weight	78.2 kg	78.2 kg
Certifications		
Safety	IEC 62109-1/-2, EN 61000-6-1/-2/-4, EN 61000-3-11/-12, EN 55011 group 1, class A EN 62920 Emission class A/Immunity class A UL62109-1, UL1741 Sup SB CSA-C22.2 No.107.1 CSA-C22.2 No.62109-1, CSA-C22.2 No.62109-2	IEC 62109-1/-2, EN 61000-6-1/-2/-4, EN 61000-3-11/-12, EN 55011 group 1, class A EN 62920 Emission class A/Immunity class A UL62109-1, UL1741 Sup SA/SB CSA-C22.2 No.107.1
Grid connection rule	overview see homepage / download area	

[1)] Power derating at high ambient temperatures

Versions	S	XL
Number of DC inputs	1 - 2	1 - 2
DC switch	-	✓
DC SPD	Type 1 + 2	Type 1 + 2
AC SPD	○	○
RS485 interface SPD	○	○
Ethernet interface SPD	○	○
PID Set	○	○

standard = ✓ upgradeable = ○